

Specifications

MAIN CAMERA

LENS	f=4.0mm - 48.0mm - F3.2-3.6
FRAME RATE	30 fps
SHOOTING AREA	1080i / max. 17.1" x 9.5" XGA / max. 17.1" x 12.7
ZOOM	12x Optical / 8x Digital
FOCUS	Manual / Zoom Sync
IMAGE PICK-UP DEVICE	1/2.8" CMOS 3.4mil pixels
TOTAL PIXELS	H: 2144 / V: 1588
EFFECTIVE PIXELS	H: 1920 / V: 1440
ANALOG RGB OUTPUT	XGA: 1024 x 768 @60Hz
HDMI OUTPUT	1080i / 720p
WHITE BALANCE	Auto / Natural Light / Fluorescent Light / Incandescent Light
BRIGHTNESS CONTROL	Auto / Manual
IMAGE MODE	Document / B&W / Photo
FLICKER CORRECTION	60Hz / 50Hz
ILLUMINATION LIGHT	White LED

GENERAL

POWER SOURCE	DC5V (AC Adapter AC100 - 240V)
POWER CONSUMPTION	7.0W
DIMENSIONS	W15.4" x D9.1" x H16.8" (Setup) W7.2" x D9.1" x H19" (Folded)
WEIGHT	5.29lbs
OUTPUT TERMINAL	RGB Input Mini Dsub 15P connector, female x 1 HDMI output terminal x 1
EXT. CONTROL TERMINAL	USB Device (2.0 compliant) Mini-B receptacle x 1

Contact us

For more information visit
www.elmoussa.com

Phone:
516.501.1400
1800.947.ELMO

Email:
elmo@elmoussa.com

ELMO

Full HD



Flexible



96x Zoom



LX-1

Visual Presenter



Present
With Ease



www.elmoussa.com



Full HD Image

The LX-1 has an HDMI output and a specially crafted lens for full HD image quality. It captures moving images at 30fps for truly smooth natural movements.



96x Zoom Capability

With 12x optical and 8x digital zoom, the LX-1 is capable of an incredible 96x zoom. Allow yourself to see detail the human eye cannot.



Flexible

The LX-1 can twist, bend and fold, giving you the ability to view objects from the top, side and up close. The LX-1 can easily convert for left handed users.



Outputs

USB, HDMI & RGB Outputs



Zoom Dial & Auto Focus

Easy access to zoom dial & auto focus button



Security Base Plate

Base plate for security & extra stability

