



The PX Series.

Platform Document Cameras.

Connect with Minds Everywhere.

The PX series platform document cameras are perfect for presenting to a large audience. Engage minds in-person or online in lecture halls, courtrooms, medical facilities, museums, military operations, and in corporate boardrooms. Designed and built to meet the requirements of ever-changing hybrid connectivity environment.

Industries Connected by PX Series.



Education

Legal & Courtroom Government





Healthcare



Corporate

Worship

"In my previous position at a state university, we standardized on ELMO document cameras for many years across all of our 350 classrooms and multiple meeting rooms. The reason for choosing ELMO was primarily the depth of the product line and quality of the products. The biggest thing that kept us coming back was the outstanding support (sales and tech) we received from our ELMO representatives. It's clear that ELMO has customer satisfaction at the center of their operation." - Douglas S., Director, Learning Spaces and Audio/Visual Technologies

Ergonomic Design and Intelligent Functions.

We've simplified camera control on the PX series with a touchscreen navigation panel, jog dial with autofocus, and an all-new 5" high resolution LCD preview monitor that features touch-based depth of field autofocus.



Present Your Way.

Keep your eyes engaged with the audience, not buttons. The platform also doubles as a dry-erase board.



Choose Your Shooting Mode.

The PX series comes with a variety of shooting modes including 4:3, widescreen 16:9, and a capture area of up to A4 portrait and A3 landscape.

Folds for Easy Storage.

Folds down to less than 4 inches in height to easily fit in a podium or drawer to be hidden away safely and securely.



Show Unparalleled Image Quality.

Capture Every Detail.

You can zoom with less deterioration of quality. Zoom up to 288x (12x digital, 12x optical, 2x sensor).

12MP CMOS Sensor.

Capture high-definition video in up to 4K (PX-30E) or 2K (PX-10E). Every detail can be accurately reproduced with unbeatable clarity.

Present with Vivid Color.

The PX series comes with a specially-crafted lens that produces the richest spectrum of colors on ELMO cameras.

Versatile Connectivity.

Multiple video inputs and outputs provide flexible connectivity options for any situation.

Integration Made Easy.

Connect to any control system via RS-232, IP on RJ45 (PX-30E only) and HDBaseT (PX-30E only) for ease of use and management.





Industry Leading Five Year Warranty.

Crafted to the highest level of quality and built to last. Peace of mind should something happen, accompanied by an outstanding support team to assist you along the way.



Save Files For Later.

Capture images or record videos to the internal memory, SD card, USB thumb drive or external hard drive (side panel).



First-Class Customer Care.


If you have any questions or need assistance with your device, our friendly staff is here to assist you.


Specifications.

PX-30E (1375)

PX-10E (1376)

Camera	
Image Sensor	1/2.3" CMOS
Effective Pixels	8.3M (3840x2160 @ 16:9 aspect), 9.3M (3520x2640 @ 4:3 aspect)
rame Rate	Max. 60fps @ FHD, 30fps @ 4K Max. 60fps
oom	Optical 12x + Sensor 2x + Digital 12x = 288x
ns/Max Aparture	F=3.2 ~ 3.88
cus Range	Wide 2″ ~ ∞, Tele 8″ ~ ∞
cus Control	Auto (one push) / Zoom Sync / Manual / Area Focus by touch
ooting Area	18.5" x 10.2" @ 16:9 aspect, 17" x 12.6" @ 4:3 aspect Possible to shoot A3 format
solution	4K (3840x2160) via HDMI Full HD (1920x1080)
er Interface	
) Display	5" Touchscreen
om Key	Yes (On Stage and Camera Head)
o Focus Button	Yes (On Stage and Camera Head)
s-through	Yes (HDMI/RGB)
hting	
-	White LED
dable Mechanical Arm	Yes
justable Arm/Head	Yes/Yes
rated Stage	Yes (Writable)
age Rotation	90°/180°/270°
eze Frame	Yes
notation	Yes by PC software
nparison	Yes by PC software
sk	Yes
ording	Yes (Photo/Video)
yback Capability	Photo: JPG Video: MP4
tional Apps	ELMO Interactive Toolbox, ImageMate + C. Available at
Alonal Apps	www.elmousa.com
nnical Interface	
B	x2 (Type A, Version 2.0) , x1 (Type B, Version 3.0)
MI	In x2 / Out x1 (Type A, Version 1.4)
8	In/Out x1
4	x1 -
232C	x1
Base T Out	x1 -
lio Out	x1
In	x1
Slot	x1
ers	
lt-in Speaker	(Operation sound only)
mote Control	Yes
curity Lock Slot	Yes
wer	DC12V DC12V
wer Consumption	21W 19W
nensions	11.7" x 19" x 18.8" (Set-up), 11.7" x 19" x 3.75" (folded)
ight	Approx. 11lbs. (Main unit)
cessories	AC Adapter, USB Cable (version 3.0), Remote Control & battery, Whiteboard sheet, Melamine Sponge, Cable Ties x3, HDMI Cable Fixture x3, Screw x3, Quickstart Guide, Instruction Manual
ptional Accessories	nature as seren as guicestare outde, instruction manual
A-2 Wireless Tablet	Yes by PC software
	-
/arranty	5 Years





CONNECTING MINDS

ELMO USA Corp. 6851 Jericho Turnpike Suite 145 Syosset, NY 11791 www.elmousa.com 516-501-1400

*Specifications subject to change without notice.